


### Hanze F2A Gravity Base Structure

Underbase grouting for the 83.5m tall, 9,000 tonne steel gravity base structure in the North Sea

Leaders in foundation and structural grouting for the global offshore energy industry





## Underbase grouting for the steel foundations of the largest field in the Dutch North Sea

#### **ABOUT THE HANZE F2A FIELD**

Hanze was the largest field to be developed in the Dutch North Sea. The development is a steel-gravity based production and storage platform. Hanze is located in block F/2 in the Dutch sector, North Sea. The field has reserves exceeding 34 million barrels of oil, as well as 40bcf of associated gas. The field covers 4.5km<sup>2</sup> between 1,340 and 1,478m below sea level.

#### **GRAVITY BASE STRUCTURE DESCRIPTION**

The foundation is of steel construction and gravity base design. It contains 12 central oil storage cells, whilst the cells to the North and South ends of the structure are used for ballast water. The void formed between the underside of the base and the seabed was filled with a sodium silicate/cement grout in order to ensure an even load distribution between the structure and the seabed. The structural integrity of the platform was dependent on the correct placement and retention of good quality grout in the voids beneath the base.

#### **QUALITY CONTROL**

During mixing, the slurry density was monitored by densitometers mounted on the mixer units. The slurry density was also monitored at intervals using a pressurised slurry density balance.

One sample was taken during the grouting of each compartment. For each sample the slurry density was measured and recorded three 75 mm grout cubes were manufactured. Each cube was marked to identify the platform, compartment number, time and date of casting and the specific gravity.

The samples were cured underwater at 8  $^{\circ}$ C ± 0.5  $^{\circ}$ C until removed for testing. All cubes were tested at age 28 days. Periodic bleed tests were also undertaken using graduated glass measuring cylinders. These were filled with 200ml of grout and a reading of the grout level was taken every 30 minutes for the next four hours.

#### THE MIXING SYSTEM

Compartment grouting was carried out in pairs, with two penetrations in the dividing cell wall to permit grout flow between the first and second compartment of each pair. One primary and one secondary grout line was provided for each pair of compartments, together with two 8" outlet ports located in the outer wall of the second compartment.

Cement was stored in bulk pressurised silos and delivered to a surge tank above the mixer. Water was delivered to the mixer from the vessel firemain pipework and measured into the mixing tank through a mechanical flowmeter. Water entered the mixer through a high pressure jet and cement through a rotary valve at a fixed rate. Sodium Silicate was added via a flow meter through the water jet in a fixed proportion to the water flow rate. The grout was transferred to a ten barrel

#### **Key Project Facts**

Operator Contractor Region Water depth Total cement Total sodium silicate Crew size Equipment Grout specification Curing temperature Mobilisation port Installation vessell	Veba (now Petro-Canada) SMIT Maritime Contractors Netherlands -43m 606.18 tonnes 58,191 litres 8 Grout mixer and pumps 2 x 100 t capacity silos 3 x Sodium Silicate tanks Workshop and Lab Umbilical Winch and Hose 3 x Grout Density probes 0.175 MPa @ 28 days 8°c Rotterdam, Netherlands North Prince
	NOITIPHILLE





The Hanze F2A Gravity Base Structure in situ

capacity tank from where it was drawn off by the pump and delivered to the GBS via a flexible hose. The grout was mixed and pumped at a rate of between 40-45m<sup>3</sup> per hour. This rate was restricted by the water supply from the vessel.

Grout pumping continued until the theoretical volume required to fill the void had been pumped, and good quality grout flow from the outlets had been confirmed by ROV.

#### **THE ENGINEER'S PERSPECTIVE**

Grouting was proceeding well until contingency procedures had to be implemented to successfully fill a number of the compartments.

During filling compartments 101+140, 61+20 and 71+30 it was reported by ROV that the grout was leaking into the adjacent compartments 102, 62 and 72, under the dividing cell walls. These compartments were not designed to be grouted. Together with 112, these were intended for later use during the de-ballasting and removal of the GBS at the end of its life. However, due to this leakage, an additional 50m3 of grout needed to be pumped into each of the leaking pairs to completely fill them and produce good returns from the grout outlet.

No flow was detected by ROV from the grout outlets during filling of compartments 91+130. After approximately 114m3 of grout had been pumped the ROV reported that flow was actually coming from the outlet of 121+160 which had been grouted 5 hours previously. Pumping was then transferred to the secondary grout line, and grouting was successfully completed.

During grouting via the line marked 100+92, the ROV reported that compartments 110+122 were actually being filled. The hoses had been incorrectly labelled. We completed grouting this compartment and moved to fill 100+92 via 110+122's grout line.

> Visit www.foundocean.com for more case studies

# FOUNDOCEAN

#### Europe

FoundOcean Ltd. Headquarters Liston Exchange Liston Court Marlow Buckinghamshire SL7 1ER United Kingdom Tel: +44 1628 567 000

#### FoundOcean

World Trade Center City Airport Bremen Hermann-Köhl-Straße 7 28199, Bremen Germany Tel: +49 421 9601 250

#### Asia & Australasia

Ambico FoundOcean Grouting Services #701-702, Shri Sai Corporate Park Next to Polaris Tower Opp. Laxmi Nagar Industrial Estate Goregaon Link Road, Goregaon (W) Mumbai 400 090 India Tel: +91 22 2876 6641

#### IEV Group Sdn Bhd

Level 22 PJX-HM Shah Tower No.16A Persiaran Barat 46050 Petaling Jaya Selangor Malaysia Tel: +6 7931 9921

#### Tamboritha Consultants

32 Jessie Lee St, Henderson 6166 Western Australia Australia Tel: + 61 8 6595 5200

#### Americas

FoundOcean, Inc. 11490 Westheimer Suite 850 Houston Texas, 77077 United States Tel: +1 713 425 6326

#### Middle East

FoundOcean 14th Floor Gold Tower Cluster I Jumeirah Lakes Towers Dubai U.A.E. PO Box 487286 Tel: + 971 4 424 9100

#### Offshore Service Bases

Europe Livingston, Scotland Middle East Jebel Ali, United Arab Emirates South East Asia Batam, Indonesia and Navi Mumbai, India Americas Houston, Texas

#### About FoundOcean

FoundOcean is the world's largest dedicated offshore construction grouting company with nearly 50 years' experience of subsea grouting for oil and gas and offshore renewables construction firms.

FoundOcean also provides life extension solutions for offshore structures which include inspection, repair, and maintenance services, marine growth control products, fabric formwork grout bags, and pipeline/cable support and protection services.

And that's why, to offshore installation contractors, FoundOcean is the subcontractor of choice to reduce their project risks.

www.foundocean.com